

Emergency Stop (E-Stop) Unit

The AL-9504-2 Emergency Stop (E-Stop) Unit provides a central connection point for external emergency stop panic buttons and positioner controllers that are located throughout the system. In the event of an emergency stop, the AL-9504-2 will command the appropriate positioner controller to disconnect motor drive power on all axes. This unit is designed to disable up to five controllers and can support up to four external E-Stop panic buttons.

AL-9504-2



AL-9504-PENDANT



Applications

- General Purpose Positioning Subsystems
- Remote Emergency Stop Support

Product Highlights

- Up to 4 External E-Stop Switch Inputs
- Up to 5 Outputs for Controller Interlock
- OSHA Compliant

Front Panel

- AC Power On/Off
- Emergency Stop (E-Stop)
- E-Stop Indicator
- Driver Indicator

Supplied Accessories

Digital Documentation Set

- User Manual (Installation, Setup, Operation)

Cables

- AC Power Cord, IEC-320 (F) to Plug

Options

- AL-9504-PENDANT - E-Stop button with 10m cable
- Opt. 101 - Additional Manual Set

- Standard □ Optional

Specifications - AL-9504-2 E-Stop Unit

| PARAMETER | POSITIONER MODEL |
|-----------|------------------|
| | AL-9504-2 |

OPERATIONAL

| | |
|-----------------------------------|---|
| Front Panel Controls & Indicators | <ul style="list-style-type: none"> • AC Power On/Off • Emergency Stop (Latching Panic Button) • E-Stop Indicator • Driver Indicator |
|-----------------------------------|---|

ELECTRICAL

| | |
|-----------------------------------|--|
| AC Input Power | 115/230 VAC +/- 10%, 50/60 Hz, single phase |
| Power Dissipation | 60 Watts |
| Remote E-Stop Channels (Pendants) | 5 |
| AL-9504-Pendant | Switches & Interconnect Cables Purchased Separately |
| Compatible Products | <ul style="list-style-type: none"> • AL-48061, AL-48062, AL-48063 • AL-4162, AL-4164, AL-4166 • AL-4147-2, AL-4107-2-6A |

PHYSICAL

| | |
|------------|--|
| Dimensions | <ul style="list-style-type: none"> • 19.0 in (48.3 cm) Width • 5.25 in (13.3 cm) Height • 11.0 in (28.0 cm) Depth |
| Weight | 10.3 lbs (4.7 kg) |

ENVIRONMENTAL

| | |
|-----------------------|----------------------------------|
| Operating Temperature | 41° to 122° F (5° to 50° C) |
| Storage Temperature | - 13° to 167° F (- 25° to 75° C) |
| Relative Humidity | 70% |



Contact your local sales representative for more information

salesteam@mvg-world.com

www.mvg-world.com/positioners